

United States Patent [19]
Andolfi

[11] Patent Number: **5,411,044**
[45] Date of Patent: **May 2, 1995**

[54] **PATIENT TRANSFER WALKER**

[76] Inventor: **Alexander S. Andolfi, 17 Sharon Ave., East Setauket, N.Y. 11733**

[21] Appl. No.: **226,506**

[22] Filed: **Apr. 12, 1994**

[51] Int. Cl.⁶ **A46B 3/00**
[52] U.S. Cl. **135/66; 135/67;**

135/75; 601/5; 280/87.05; 5/86.1; 414/921
[58] Field of Search 135/66, 67, 69, 70,
135/72, 75, 73; 280/304.1, 250.1, 87.05; 601/5,
23, 24; 5/86.1, 81.1, 83.1; 414/921

[56] **References Cited**

U.S. PATENT DOCUMENTS

2,792,052	5/1957	Johannesen	5/83.1 X
3,189,345	6/1965	Simpson	272/70.4
3,374,493	3/1968	Herrera	5/86
3,596,298	8/1971	Durst, Jr.	5/81
3,629,880	12/1971	Van Rhym	5/86
4,054,319	10/1977	Fogg et al.	297/384
4,248,256	2/1981	Thomas	135/67
4,390,076	6/1983	Wier et al.	280/304.1 X
4,443,902	4/1984	Baer	5/81
4,598,944	7/1986	Meyer et al.	280/304.1 X
4,704,709	11/1987	Slebzak et al.	367/158
4,704,749	11/1987	Aubert	5/81
4,748,994	6/1988	Schultz et al.	135/67
4,802,542	2/1989	Houston et al.	180/65.5
4,809,804	3/1989	Houston et al.	180/65.6
4,985,947	1/1991	Ethridge	5/81
5,040,556	8/1991	Raines	135/67
5,117,516	6/1992	Penner	5/86

FOREIGN PATENT DOCUMENTS

345114	4/1960	Switzerland	135/67
1078758	8/1967	United Kingdom	5/86.1

OTHER PUBLICATIONS

The Arjo-Century Lift Ride Chair, Arjo-Century, Inc., Morton Grove, Illinois 60053, undated.
Stand-Aid of Iowa, Inc.-advertisement.
Motion Systems Corp.-Ball Drive Actuator 85151/85152 Undated-advertisement.

Primary Examiner—Lanna Mai
Attorney, Agent, or Firm—Alfred M Walker

[57] **ABSTRACT**

A walker for a handicapped person has a pair of base rails juxtaposed, and a pair of front posts extend therefrom. Each front post is attached to a front of a respective rail. A first pair of rotation-changeable motors drives a pair of actuators, initially pointing upwardly. A first pair of gear reduction devices, which in combination with a pair of rear posts, can be rendered tiltable, has respective input shafts coupled to respective output shafts of the motors. The pair of tiltable rear posts are extendable or retractable by rotation-sense selection of the first pair of motors. A pair of crutch supports are in contact with the rear posts, Which fit under the armpits of the handicapped person. A pair of levers which extend outwardly and downwardly from the pair of crutch supports, respectively, are bent rearwardly, and equipped with handles. A second pair of rotation-changeable motors are attached to the pair of front posts, respectively, and a second pair of length-adjustable gear-reduction mechanisms are coupled to the second pair of motors, and also to the pair of the rear posts, respectively, so as to be operative, upon length adjustment, between forward-and rearward-positions. A switch is connected to the first and second pairs of motors for separate selection of the height and inclination of the rear posts, respectively, by selective choice of the motor's sense-of-rotation and travel.

16 Claims, 12 Drawing Sheets

